

BIPASS INSTALLATION INSTRUCTIONS

1. Measure door opening and trim the pre-cut metal track for an exact fit.
2. **LEVEL THE TRACK.** Do not place track flush with face of wall. Set at least 1/2" back before anchoring it to the ceiling or header. It is important that the track is level for doors to operate properly. Holes for fasteners are pre-drilled for correct spacing.
3. Position the "Adjustable Hanger Brackets" on the back side of each door panel, midway in the Flange Lock slot. (2 Brackets per door.) Attach Hanger Bracket to door with a #8 X 5/8" phillips head screw in the center of the elongated screw opening.
4. Hang rear door panel (s) first by tilting the bottom of the panel outward (into the room) and place the Hange Bracket Rollers onto the rear track glide.
5. Hang the front panel (s) in the same manner, placing the Hanger Bracket Rollers onto the front track guide.
6. Align door panels for a pleasing vertical line by sliding a Hanger Bracket, either the right side or left side bracket, upwards on the door panel. (Loosen the attachment screw slightly to move the hanger upward.) When the door is in alignment, tighten the attachment screw and install 2, # 8 X 5/8" screws in the round holes to permanently affix the Hanger Brackets to the door panel.
7. Install the #116 Floor Guide by screwing it to the floor. Position guide so that both front and back doors are into the guide when the doors are in a closed position. (There is a 1" overlap of door panels when in a closed position.)
8. Install the round flush pulls in pre mortised hole in the face of each panel.
9. Install the rubber tipped Door Stop on back side of the **FRONT DOOR PANEL**, 4" from vertical outside edge of the door panel and above the door pull area.